Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The following on-road motor vehicles with a manufacturer's GVWR over 14000 pounds are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

			_			ENGINE D	ESCRIPTION					
	E	EXECUTIVE		EL	IGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE 1	STANDARDS & TEST	INTENDED SERVICE	ECS & SPECIAL FEATURES		
MANUFACTURE	ORDER		YEA	R E	NGINE FAMIL I			PROCEDURE	CLASS 2			
FORD MOTOR COMPANY	Α-	A-010-1387-1		7 71	MXH05.4BSA		Gasoline	Otto	нро	2TWC, TWC, 2HO2S, SFI		
Gasoline, LPG o	r Alcoho	l Vehicles O	nly				VEHICLI	E DESCRIPTION	Marie Marie	A transfer of the second		
EVAPORATIVE		FUEL TANK CAPACITY		VEHIC		VEHICLE M.	HICLE MAKE & MODELS		ENGINE MODELS / CODES (rated power, in hp)			
FAMILY	UL (K)	(gallon		MODE				(L) 5.4				
FMXE0265GAT	150	55		2007		E-450 Strip Chassis			7E414Y0508, 7E414Y0510 (255)			
	*	+		*		*			*			
•				*		*			•			
				-			*		i	•		
				-			*	•	•			

* =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=title; K=1000 miles; hp=horsepower; kw=kilowatt; CNGLNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=mutti fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; CNGLNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=mutti fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel; LMMH HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDD=heavy duty Offic; LMMH HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDD=heavy duty Offic; SCS=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefitx) =warm-up catalyst; DFF=diesel particulate filter; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a. universal or linear oxygen sensor); TBI=throttle body fuel injection; SFI/MFI=sequential/mutti port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charge; CAC=charge air cooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; (2004may28)

Following are: 1) the FTP exhaust emission standards or family emission limit(s) as applicable under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.)

	NMHC		NOx		NMHC+NOx		co		PM		нсно	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
TD	 		*	· ·	*	•	37.1	•	•	*	•	•
EL	+	•		-	0,85	*	*	•	*	•	*	+
ERT	+ •	*	•	•	0.76	*	4.3	•	*		•	•
ITE	 	•		•		*		*		•		*

g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle; NTE=Not-to-Exceed emission limit; STD=standard or emission lest cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed vehicle models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels), 13 CCR 1976(b)(1)(F) {evaporative emission standards}, 13 CCR 2035 et seq. (emission control warranty), and 13 CCR 2235 [fill pipes and openings of motor vehicle fuel tanks]. (The braces {} are for gasoline, LPG or alcohol fueled vehicles only. The brackets [] are for gasoline or alcohol fueled vehicles only.)

Vehicles certified under this Executive Order must conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-010-1388 dated September 19, 2006.

day of November 2006. Executed at El Monte, California on this

Annette Hebert, Chief

Mobile Source Operations Division